Reference

CC-4

4-channel stereo amplifier

CC-4 is a small and powerful amplifier with a RMS power output of 4 x 70 Watts.
In 4 ohm mono bridge-connection, it puts out all of 2 x 140 Watts.

- Built-in low-pass filter for subwoofers, variable between 50 and 500 Hz.
- The high-pass filter is also variable between 50 and 500 Hz.
- Built-in protection circuits shut down the amplifier in the event of overloads.
- High level input with AUTO-start function
- Bass EQ variabel from 0 till +6dB.
- THD at 5W, 1 kHz: <0,02%
- Damping factor: >250
- Signal to noise ratio, A-weighted: 110 dB

Specifications

	CC-4
Number of channels	4
Amplifier class	AB
Power output RMS in 4 ohm	4 x 50 W
Power output RMS in 2 ohm	4 x 70 W
Power output RMS 4 ohm bridged	2 x 140 W
Signal to noise ratio, A-weighted	110 dB
Damping factor	>250
THD @ 5 W, 1 kHz	< 0,02%
Frequency response	10 Hz - 505 kHz
Input impedance, low level	6 kohm
Input sensitivity	1 - 4V
Input impedance, high level	45 ohm
High level input	Yes
Filter high-pass adjustable	50 - 500 Hz*
Filter low pass adjustable	50-500 Hz*
can be switched in/out	
Bass EQ @ 60 Hz	0 - +6 dB
Power consumption, idle	0,5 A
Power consumption, max	43A
Fuse	Internal fuse 40 A
Dimensions HxWxD(mm)	51 x 129 x 250
Dimensions (inch)	2 x 5,07 x 9,85
Weight	1,8 kg

Sound tuned in England

DLS Sweden
www.dls.se
E-mail. info@dls.se